



## Sunglorin G 145

Self-gloss emulsion



### Area of application

- For coatable and water-resistant floor coverings such as sealed parquet, linoleum, PVC and rubber
- Natural and artificial stone

### Product properties

- Can be used as wiping care
- Easy removability
- Polishable with the single-disc machine
- Good dispersive capacity
- Slip-resistant according to DIN 51131
- Suitable for cleaning

### Application and dosage

- Always use cold water.
- Requirement: Thoroughly cleaned, neutralised and dry floor covering.
- Floor covering must be free of surfactants.
- Apply undiluted a thin layer in 2 – 3 layers.
- Consumption: 25 - 35 ml / per m<sup>2</sup> / per order



undiluted



1:1 with water



100 - 200 ml / 10 l water

### Note


- Protect from frost.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- Avoid direct sunlight.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at [www.buzil.com](http://www.buzil.com).
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

### Further information

- **Product colour:** white
- **GISBAU code:** GE 10
- **UFI code:** VA20-U0F9-Y00M-PXU4
- For professional use only.

### Sales units

- G145-0010RA: 1 x 10 l canister
- G145-0001RA: 12 x 1 l bottle



Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.