



## Corridor® Basic S 720

Pore filler and primer



### Area of application

- For open-pored and absorbent floor coverings, e.g. concrete, cement and magnesite screed
- Particularly suitable for old and damaged floor coverings, as well as linoleum coverings that have been thoroughly cleaned several times

### Product properties

- Prolongs value retention
- Penetrates deep into the pores
- Protects against dirt build-up and is permeable to water vapour
- Resistant to alcohol and disinfectants
- Chemically insoluble
- Dust-binding
- Deepens the colours
- Makes the daily routine clean easier
- Resistant to mechanical influences

### Application and dosage

- Always use cold water.
- Apply undiluted in 1 - 3 layers (linoleum), for absorbent coverings such as concrete, dilute the first layer of screed 1:1 with water.
- Consumption: 25 - 35 ml / per m<sup>2</sup> / per order



1:1 with water  
- undiluted



Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

### Note

- Protect from frost.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- Avoid direct sunlight.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at [www.buzil.com](http://www.buzil.com).
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

### Further information

- **Product colour:** white
- **GISBAU code:** GE 10
- **UFI code:** 14A0-W08E-U00P-V0V0
- For professional use only.

### Sales units

- S720-0010RA: 1 x 10 l canister