



# Budenat® Alkasept D 445

High-alkaline disinfectant cleaner



## Area of application

- For surface disinfection in public institutions, in the food industry and in the food processing industry, as well as in the kitchen area and in the healthcare sector, etc.
- For all water- and alkali-resistant surfaces, materials and floor coverings

## Product properties

- Cleaning and disinfection in one step
- Very good cleaning effect
- Effective against bacteria, yeasts, moulds and enveloped and non-enveloped viruses
- Spectrum of activity: bactericidal, yeasticidal, virucidal
- Strong oil and grease-removing power
- VAH and IHO listed
- Meets the requirements within the framework of an HACCP concept
- Halal certified according to HALAL CONTROL

## Application and dosage

- Recommended use for surface disinfection (spectrum of effects/exposure times):
- bactericidal, yeasticidal – VAH / EN 13697: high load, with mechanics 5 min. 6.0%, 15 min. 2.0%, 30 min. 1.0%
- bactericidal, yeasticidal – EN 16615: low and high load 1 min. 2.0 %
- fungicidal – EN 1650: low load 30 min. 4.0 %
- virucidal – EN 14476 and EN 16777: low load 60 min. 5.0 %
- limited virucidal – EN 14476 and EN 16777: high load 5 min. 4.0%, low load 1 min. 4.0%
- limited virucidal PLUS – EN 14476 and EN 16777: low load 30 min. 5.0 %
- First remove coarse dirt from the surface.
- We then recommend using suitable wet mopping methods.
- Let it dry or rinse after the exposure time has elapsed.



100 - 600 ml / 10 l water

- Apply fresh application solutions and consume them within 24 hours at the latest.

## Note

- Ingredients: 100g contains: 6.9g didecyl dimethyl ammonium chloride.
- Surfaces that come into contact with food or the skin must be rinsed with drinking water after disinfection.
- Absorb unintentionally released product with liquid-binding material (sand, diatomaceous earth, universal binder).
- Do not allow the product to enter the sewage system or water bodies undiluted.
- Contribute emptied packaging to recycling.
- Use disinfectants carefully. Always read the label and product information before use.
- Recommended storage temperature: 5 - 25 °C.
- Consume opened containers within 9 months.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at [www.buzil.com](http://www.buzil.com).
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

## Further information

- **Product colour:** colourless - light yellow
- **GISBAU code:** GD 40
- **UFI code:** 4G10-S0JA-W00P-2J0G
- For professional use only.

## Sales units

- D445-0010RA: 1 x 10 l canister
- D445-0001RA: 12 x 1 l bottle



Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.