

Total G 424

Basic cleaner, highly alkaline











Area of application

 Alkali and water-resistant hard floor coverings such as PVC, stone (unpolished), clinker and clay tiles

Product properties

- Very good film-removing action
- Removes stubborn dirt
- Suitbale for use in cleaning machines
- Low-foaming
- Very good wetting properties

Application and dosage

- Always use cold water.
- Spread cleaning solution on the floor, let it briefly take effect, clean thoroughly, vacuum the loosened dirt, remove residues.
- Rinse the floor covering with clean water.
- Consumption: 100 250 ml / per m²



10 I water

 Apply fresh application solutions and consume them within 24 hours at the latest.

Note

- Before application, check the surface for colour fastness in a hidden area.
- Not suitable for alkali-sensitive floor coverings such as linoleum, rubber, open wood, cork, limestone such as marble and terrazzo.
- When used in the machine, the tanks should be cleaned and rinsed regularly.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- Safety: Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- Storage: Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- Environmental: Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

• Product colour: golden yellow

• GISBAU code: GG 80

■ UFI code: 04X0-R0T5-J001-2FN8

For professional use only.

Sales units

• G424-0010RA: 1 x 10 l canister



